

Altronix®
Netway®
SPECTRUM

**DEPLOY IP DEVICES IN
REMOTE LOCATIONS**
WITH OR WITHOUT LOCAL POWER



Altronix®

BACKED BY A LIFETIME WARRANTY



The NetWay Spectrum series by Altronix takes fiber and power to a new level. Indoor and outdoor models include hardened PoE switches and multi-port media converters with or without integral power. Units can be deployed with conventional single or multi-mode fiber... or hybrid cable which combines fiber with copper to simultaneously deliver power and data. NetWay Spectrum also features LINQ™ Network Management Technology to remotely monitor, control and report power/diagnostics from anywhere over the network. **Go further with NetWay Spectrum from Altronix.**

- **NetWay Spectrum** is the solution for deploying IP devices in remote locations with or without local power, utilizing fiber optic infrastructure.
- **NetWay Spectrum** is designed and manufactured for use in harsh environments at greater distances.
- **NetWay Spectrum** offers a series of hardened PoE switches with optimized Lithium Iron Phosphate (LiFePO4) battery backup.
- **NetWay Spectrum** comes in a wide range of models for indoor and outdoor applications.
- **NetWay Spectrum** hardened PoE switches, media converters and power supplychargers are available pre-configured or separately, as subcomponents to customize your system.
- **NetWay Spectrum** features embedded **LINQ™ Network Management Technology** to remotely monitor, control and report power/diagnostics – streamlining service and maintenance operations by leveraging the network. A built-in timer can reset devices automatically on a schedule.
- **NetWay Spectrum** products are TAA compliant, NDAA compliant and backed by a Lifetime Warranty.



*Scan here
to view video*




Merging infrastructure with emerging technology.™

Configuration options


Switch in NEMA 4/4X Small Outdoor Enclosure	Switch in NEMA 4/4X Outdoor Enclosure	Switch and Power Supply/Charger on Backplane	Switch and Power Supply/Charger in Outdoor Enclosure	Switch and Power Supply/Charger in Larger Outdoor Enclosure	Switch and Power Supply/Charger in Indoor Enclosure
Dimensions: 7.32"W x 9.5"H x 4.92"D	Dimensions: 13.31"H x 11.31"W x 5.59"D	Dimensions: 10.75"H x 8.875"W x 2.375"D	Dimensions: 13.31"H x 11.31"W x 5.59"D	Dimensions: 17.53"H x 15.3"W x 6.67"D	Dimensions: 13.5"H x 13"W x 3.25"D

Remote Network Power Management Technology




NetWay Spectrum features embedded LINQ™ Network Management Technology to remotely monitor, control and report power/diagnostics – streamlining service and maintenance operations by leveraging the network. A built-in timer can reset devices automatically on a schedule. Stay alert, resolve issues, and control power from anywhere over the network.

- Eliminate truck rolls and increase RMR.
- Provides local and/or remote access to critical linformation via LAN/WAN.
- Report system diagnostics via **LINQ™ Dashboard** and/or email alert notification.
- Programmable voltage and current threshold.
- Control output and power supply via flexible timing parameters.
- Power cycle mode, Timer Scheduler, FACP override, Battery backup.
- Programmable time events.
- Third-party-certified cybersecurity.
- Individual password protected user levels.
- Manage and maintain security devices over multiple sites via **Altronix LINQ™ Dashboard**.
Intuitive IP communication software solution to remotely monitor, report, and control any combination of individual or multiple groups of products across any number of locations and systems.



Hardened PoE Switches, Single SFP (Board only)

Model	SFP Port(s)	10/100/1000 Ethernet ports	PoE ports	Layer 2 Managed with Embedded LINQ™	Input: 48-56VDC
NetWay4EB	1	4	4-Ports rated up to 30W (120W total power)	✓	✓
NetWay4EBTB			4-Ports rated up to 90W (240W total power)		
NetWay4E1B			4-Ports rated up to 30W (120W total power)	—	
NetWay4E1BTB			4-Ports rated up to 90W (240W total power)		




Hardened PoE Switches, Dual SFP (Board only)

Model	SFP port(s)	10/100 Ethernet ports	10/100/1000 Ethernet ports	PoE ports	Layer 2 Managed with Embedded LINQ™	Input: 48-56VDC
NetWaySP41B	2	—	4	4-Ports rated up to 30W (120W total power)	—	✓
NetWaySP41BTB				4-Ports rated up to 90W (240W total power)		
NetWaySP4B			4	4-Ports rated up to 30W (120W total power)	✓	
NetWaySP4BTB			4	4-Ports rated up to 90W (240W total power)		
NetWaySP8B			2	6	8-Ports rated up to 30W or 2-Ports rated up to 60W (240W total power)	

Hardened PoE Switches Mounted in Outdoor Enclosure (external power required)

Model	Configuration	SFP port(s)	10/100 Ethernet ports	10/100/1000 Ethernet ports	PoE ports	Layer 2 Managed with Embedded LINQ™	Input: 48-56VDC	
NetWay4E1WPN	NEMA4/4X Rated Outdoor Enclosure	1	—	4	4-Ports rated up to 30W (120W total power)	—	✓	
NetWay4E1BTWPN		1	—	4	4-Ports rated up to 90W (240W total power)			
NetWaySP41WPN		2	—	4	4-Ports rated up to 30W (120W total power)			✓
NetWaySP41BTWPN		2	—	4	4-Ports rated up to 90W (240W total power)			
NetWay4EWPN		1	—	4	4-Ports rated up to 30W (120W total power)	✓		
NetWay4EBTWPN		1	—	4	4-Ports rated up to 90W (240W total power)			
NetWaySP4WPN		2	—	4	4-Ports rated up to 30W (120W total power)			
NetWaySP4BTWPN		2	—	4	4-Ports rated up to 90W (240W total power)			
NetWaySP8WPN		2	2	6	8-Ports rated up to 30W or 2-Ports rated up to 60W (120W total power)			



Hardened PoE Switches (Single SFP) with Power Supply/Chargers in Enclosure

Model	Configuration	SFP port(s)	10/100/1000 Ethernet ports	PoE ports	Layer 2 Managed with Embedded LINQ™	Input: 115/230VAC	Built-in Battery Charger	Enclosure Accommodates Batteries	
NetWay4E1WP	Outdoor Enclosure	1	4	4-Ports rated up to 30W (POE201 - 120W total power)	—	✓	SLA or Gel	—	
NetWay4E1WPX	Outdoor Enclosure w/Battery Shelf							✓	
NetWay4E1X	Indoor Enclosure							—	
NetWay4E1BTWP	Outdoor Enclosure			4-Ports rated up to 90W (POE240 - 240W total power)			—	LiFePO4, SLA, or Gel	—
NetWay4E1BTWPX	Outdoor Enclosure w/Battery Shelf								✓
NetWay4E1BTX	Indoor Enclosure								—
NetWay4E1BTWP3	Outdoor Enclosure			4-Ports rated up to 90W (POE360 - 360W total power)			—	LiFePO4, SLA, or Gel	—
NetWay4E1BTWPX3	Outdoor Enclosure w/Battery Shelf								✓
NetWay4E1BTX3	Indoor Enclosure								—
NetWay4ELWPX	Outdoor Enclosure w/Battery Shelf			4-Ports rated up to 30W (POE60 - 75W total power)			—	LiFePO4	—
NetWay4EWP	Outdoor Enclosure			4-Ports rated up to 30W (POE201 - 120W total power)			—	SLA or Gel	—
NetWay4EWPX	Outdoor Enclosure w/Battery Shelf								✓
NetWay4EX	Indoor Enclosure								—
NetWay4EBTWP	Outdoor Enclosure			4-Ports rated up to 90W (POE240 - 240W total power)			✓	LiFePO4, SLA, or Gel	—
NetWay4EBTWPX	Outdoor Enclosure w/Battery Shelf								✓
NetWay4EBTX	Indoor Enclosure								—
NetWay4EBTWP3	Outdoor Enclosure			4-Ports rated up to 90W (POE360 - 360W total power)			—	LiFePO4, SLA, or Gel	—
NetWay4EBTWPX3	Outdoor Enclosure w/Battery Shelf								✓
NetWay4EBTX3	Indoor Enclosure	—							


Hardened PoE Switches (Dual SFP) with Power Supply/Chargers in Enclosure

Model	Configuration	SFP port(s)	10/100/1000 Ethernet ports	PoE ports	Layer 2 Managed with Embedded LINQ™	Input: 115/230VAC	Built-in Battery Charger	Enclosure Accommodates Batteries	
NetWaySP41WP	Outdoor Enclosure	2	4	4-Ports rated up to 30W (POE201 - 120W total power)	—	✓	SLA or Gel	—	
NetWaySP41WPX	Outdoor Enclosure w/Battery Shelf							✓	
NetWaySP41X	Indoor Enclosure							—	
NetWaySP41BTWP	Outdoor Enclosure			4-Ports rated up to 90W (802.3bt) (POE240 - 240W total power)			—	LiFePO4, SLA, or Gel	—
NetWaySP41BTWPX	Outdoor Enclosure w/Battery Shelf								✓
NetWaySP41BTX	Indoor Enclosure								—
NetWaySP41BTWP3	Outdoor Enclosure			4-Ports rated up to 90W (802.3bt) (POE360 - 360W total power)			—	SLA or Gel	—
NetWaySP41BTWPX3	Outdoor Enclosure w/Battery Shelf								✓
NetWaySP41BTX3	Indoor Enclosure								—
NetWaySP4WP	Outdoor Enclosure			4-Ports rated up to 30W (POE201 - 120W total power)			—	SLA or Gel	—
NetWaySP4WPX	Outdoor Enclosure w/Battery Shelf								✓
NetWaySP4X	Indoor Enclosure								—
NetWaySP4LWPX	Outdoor Enclosure w/Battery Shelf			4-Ports rated up to 30W (POE60 - 75W total power)			—	LiFePO4	✓
NetWaySP4BTWP	Outdoor Enclosure			4-Ports rated up to 90W (802.3bt) (POE240 - 240W total power)			✓	LiFePO4, SLA, or Gel	—
NetWaySP4BTWPX	Outdoor Enclosure w/Battery Shelf								✓
NetWaySP4BTX	Indoor Enclosure								—
NetWaySP4BTWP3	Outdoor Enclosure	4-Ports rated up to 90W (802.3bt) (POE360 - 360W total power)	—	SLA or Gel	—				
NetWaySP4BTWPX3	Outdoor Enclosure w/Battery Shelf				✓				
NetWaySP4BTX3	Indoor Enclosure				—				
NetWaySP4TCW53	Large Outdoor Enclosure (WP5) w/Battery Shelf	4-Ports rated up to 90W (802.3bt) (POE360 - 360W total power)	—	Includes rapid battery charger (EBC48) SLA or Gel	✓				

Hardened PoE Switches (Dual SFP) with Power Supply/Chargers in Enclosure

Model	Configuration	SFP port(s)	10/100 Ethernet ports	10/100/1000 Ethernet ports	PoE ports	Layer 2 Managed with Embedded LINQ™	Input: 115/230VAC	Built-in Battery Charger	Enclosure Accommodates Batteries	
NetWaySP8WP	Outdoor Enclosure	2	2	6	8-Ports rated up to 30W or 2-Ports rated up to 60W (POE201 - 120W total power)	✓	✓	SLA or Gel	—	
NetWaySP8WPX	Outdoor Enclosure w/Battery Shelf								✓	
NetWaySP8X	Indoor Enclosure								—	
NetWaySP8LWPX	Outdoor Enclosure w/Battery Shelf				8-Ports rated up to 30W or 1-Port rated up to 60W (POE60 - 75W total power)			LiFePO4	✓	
NetWaySP8WP2	Outdoor Enclosure							8-Ports rated up to 60W (POE240 - 240W total power)	LiFePO4, SLA, or Gel	—
NetWaySP8WPX2	Outdoor Enclosure w/Battery Shelf									✓
NetWaySP8X2	Indoor Enclosure				—					
NetWaySP8WP3	Outdoor Enclosure				8-Ports rated up to 60W (POE360 - 360W total power)			SLA or Gel	—	
NetWaySP8WPX3	Outdoor Enclosure w/Battery Shelf								✓	
NetWaySP8X3	Indoor Enclosure								—	
NetWaySP8C3W5	Large Outdoor Enclosure (WP5) w/Battery Shelf				8-Ports rated up to 60W (POE360 - 360W total power)			Includes rapid battery charger (EBC48) SLA or Gel	✓	

NetWaySP8C3W5 - Outdoor Hardened PoE+ Switch with Integral Power and Rapid Battery Charger



Hardened PoE Switches (Single/Dual SFP) with Power Supply/Chargers on Backplane

Model	Configuration	SFP port(s)	10/100/1000 Ethernet ports	PoE ports	Layer 2 Managed with Embedded LINQ™	Input: 115/230VAC	Built-in Battery Charger	
NetWay4E1PL	Switch & Power Supply/Charger Mounted on Backplane (No enclosure)	1	4	4-Ports rated up to 30W (POE201 - 120W total power)	—	✓	SLA or Gel	
NetWay4E1BTPL				4-Ports rated up to 90W (POE240 - 240W total power)	—		LiFePO4, SLA, or Gel	
NetWay4E1BTPL3				4-Ports rated up to 90W (POE360- 360W total power)	—		SLA or Gel	
NetWay4EPL				4-Ports rated up to 30W (POE201 - 120W total power)	✓		SLA or Gel	
NetWay4EBTPL				4-Ports rated up to 90W (POE240 - 240W total power)	✓		LiFePO4, SLA, or Gel	
NetWay4EBTPL3				4-Ports rated up to 90W (POE360 - 360W total power)	✓		SLA or Gel	
NetWaySP41PL		2	4	4-Ports rated up to 30W (POE201 - 120W total power)	—		SLA or Gel	
NetWaySP41BTPL				4-Ports rated up to 90W (POE240 - 240W total power)	—		LiFePO4, SLA, or Gel	
NetWaySP41BTPL3				4-Ports rated up to 90W (POE360 - 360W total power)	—		SLA or Gel	
NetWaySP4PL				4-Ports rated up to 30W (POE201 - 120W total power)	✓		SLA or Gel	
NetWaySP4BTPL				4-Ports rated up to 90W (POE240 - 240W total power)	✓		LiFePO4, SLA, or Gel	
NetWaySP4BTPL3				4-Ports rated up to 90W (POE360 - 360W total power)	✓		SLA or Gel	
NetWaySP8PL				8	4-Ports rated up to 30W (POE201 - 120W total power)		✓	SLA or Gel
NetWaySP8PL2				8	4-Ports rated up to 90W (POE240 - 240W total power)		✓	LiFePO4, SLA, or Gel
NetWaySP8PL3	8			4-Ports rated up to 90W (POE360 - 360W total power)	✓	SLA or Gel		


Media Converters

Model	Configuration	SFP port(s)	10/100/1000 Ethernet ports	PoE Ports	Class 2 power limited Outputs	56VDC Power Output	Integral Power Supply/Charger	Power Input	Built-in Battery Charger
NetWaySP4	1U Rack Mount	4	4	Supports up to 60W max per port	—	✓	—	48-56VDC or PoE+ (30W) / Hi-PoE (60W)	—
NetWaySP4P				120W max per port (240W total power)	—		✓	115/230VAC	✓
NetWaySP4P2				60W max per port (240W total power)	✓		✓	115/230VAC	✓
NetWaySP4PX				120W max per port (480W total power)	—		✓	115/230VAC	✓
NetWaySP1BT	Modular Case (DIN Rail Mountable)	1	1	90W max	—	—	—	48VDC to 56VDC	—
NetWaySP1P			1	30W max					
NetWaySP2P			2	30W max per port					
NetWaySP1H	Modular Metal Case (DIN Rail Mountable)	1	1	90W max	—	✓	—	115/230VAC	—
NetWaySP1A	Modular Case (DIN Rail Mountable)	1	1	N/A	—	—	—	PoE (Class 1)	—
NetWaySP8A	1U Rack Mount	8	8					115/230VAC	
NetWaySP16A	1U Rack Mount	16	16					115/230VAC	


Media Converters in Outdoor Enclosure

Model	Configuration	SFP port(s)	10/100/1000 Ethernet ports	PoE ports	Input: 48-56VDC
NetWaySP1BTWPN	Outdoor Enclosure	1	1	Single Port (802.3bt) rated up to 90W	✓
NetWaySP2PWPN	Outdoor Enclosure		2	2-Ports rated up to 30W	

NetWaySP2P - 3-Port Media Converter/Switch



NetWaySP1BTWPN - Outdoor Single Port Media Converter






Media Converters with Power Supply/Chargers in Outdoor Enclosure

Model	Configuration	SFP port(s)	10/100/1000 Ethernet ports	PoE ports	Input: 115/230VAC	Built-in Battery Charger	Enclosure Accommodates Batteries
NetWaySP1BTWP	Outdoor Enclosure	1	1	Single Port (802.3bt) rated up to 90W	✓	✓	—
NetWaySP1BTWPX	Outdoor Enclosure w/Battery Shelf						✓
NetWaySP2PWP	Outdoor Enclosure		2	2-Ports rated up to 30W			—
NetWaySP2PWPX	Outdoor Enclosure w/Battery Shelf						✓




Ethernet to Fiber Media Converters


NetWaySP4P / NetWaySP4P2 / NetWaySP4PX - 4-Port Media Converters with Integral Power/Charger




NetWaySP1H - Single Port Powered Media Converter




NetWaySP8A - 8-Port Media Converter (16-Port version available)



NetWaySP4PX Application Generating Power from the Head-End to Remote NetWay Spectrum PoE Switch



NetWaySP8A Application Utilizing Local Power at Remote NetWay Spectrum PoE Switches



Power Sources for NetWay Spectrum

Model	Description	Input	Total Output Power	Built-in Battery Charger	Dimensions (LxWxH)
POE60	Single Output Power Supply/Charger	115/ 230VAC	56VDC / 75W	Charges LiFePO4 Batteries	4" x 7.19" x 2" (board only)
POE201			56VDC / 120W	Charges SLA or Gel	4" x 7" x 1.375" (board only)
POE240			56VDC / 240W	Charges LiFePO4, SLA, or Gel	4.5" x 7.75" x 1.375" (board only)
POE360			54VDC / 360W	Charges SLA or Gel	4.5" x 7.75" x 1.375" (board only)

Accessories for NetWay Spectrum

Model	Description
BTL125	Rechargeable Lithium Iron Phosphate (LiFePO4) battery provides optimal backup. Smart technology - low power disconnect, 10 years shelf life, Up to 5,000 duty cycles and Environmentally friendly. 
EBC48	External Rapid Battery Charger (48VDC) charges 40Ah or larger batteries in under 8 hours. Used with POE240/POE360 power supplies. 
PMK1	Pole Mount Kit fits WP1, WP3 & WP4 Altronix Outdoor Enclosures (accommodates 2" - 8" dia. or 5" square poles) 
PMK2	Pole Mount Kit fits WP2 Altronix Outdoor Enclosures (accommodates 2" - 8" dia. or 5" square poles) 
RE2	Rack Mount Battery Enclosure (2U) accommodates four (4) 12VDC/7AH batteries. 
P1SM10	Single-mode SFP module (up to 20km). P1SM102PK: 2 pack of P1SM10 
P1MM	Multi-mode SFP module (up to 550m). P1MM2PK: 2 pack of P1MM 
P1MM2PK	Single strand SFP modules (up to 2km). 2 pack 
P1GCE	Copper SFP module (up to 100m). 
VENT2	Pair of air vents to ensure efficient air circulation and prevent water condensation. Includes template and mounting screws. 



Hardened PoE Switches Mounted in Outdoor Enclosure (external power required)


Model	Configuration	Ethernet Data port	PoE ports (10/100/1000)	Embedded LINQ™ Power Management	Input
NetWay5BTWPN	NEMA4/4X Rated Outdoor Enclosure	1	4-Ports rated up to 90W (240W total power)	—	48-56VDC
NetWay5PWPN			4-Ports rated up to 30W (120W total power)		12/24VDC
NetWay5BTQWPN		1	4-Ports rated up to 90W (240W total power)	✓	48-56VDC
NetWay5PQWPN			4-Ports rated up to 30W (120W total power)		12/24VDC




Hardened PoE Switches with Power Supply/Chargers on Backplane

Model	Configuration	Ethernet Data port	PoE ports (10/100/1000)	Embedded LINQ™ Power Management	Input
NetWay5BTPL	NEMA4/4X Rated Outdoor Enclosure	1	4-Ports rated up to 90W (240W total power)	—	115/230VAC Input
NetWay5BTQPL				✓	

NetWay5PQWP - Outdoor Hardened PoE+ Switch with Network Management



NetWay5BTPL - PoE+ Switch with Integral Power on Backplane




Lifetime Warranty

Hardened PoE Switches with Power Supply/Chargers in Enclosure

Model	Configuration	Ethernet Data port	PoE ports (10/100/1000)	Embedded LINQ™ Power Management	Input 115/230VAC	Built-in Battery Charger	Enclosure Accommodates Batteries
NetWay5BTWP	NEMA4/4X Rated Outdoor Enclosure	1	4-Ports rated up to 90W (240W total power)	—	✓	Charges LiFePO4, SLA, or Gell	—
NetWay5BTWPX	Outdoor Enclosure w/Battery Shelf						✓
NetWay5BTX	Indoor Enclosure						—
NetWay5PWP	NEMA4/4X Rated Outdoor Enclosure		4-Ports rated up to 30W (120W total power)				—
NetWay5PWPX	Outdoor Enclosure w/Battery Shelf						✓
NetWay5PX	Indoor Enclosure						—
NetWay5BTQWP	NEMA4/4X Rated Outdoor Enclosure	1	4-Ports rated up to 90W (240W total power)	✓	✓	Charges LiFePO4, SLA, or Gell	—
NetWay5BTQWPX	Outdoor Enclosure w/Battery Shelf						✓
NetWay5BTQX	Indoor Enclosure						—
NetWay5PQWP	NEMA4/4X Rated Outdoor Enclosure		4-Ports rated up to 30W (120W total power)				—
NetWay5PQWPX	Outdoor Enclosure w/Battery Shelf						✓
NetWay5PQX	Indoor Enclosure						—

NetWay5BTWP - Outdoor Hardened PoE+ Switch with Integral Power



PROTECTING CRITICAL INFRASTRUCTURE
OVER LONGER DISTANCES.

 | Altronix[®] BACKED BY A LIFETIME WARRANTY